NSN 5315-01-312-7098

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-312-7098

Shank Diameter:

Between 0.1870 inches and 0.1895 inches

Button Handle Diameter:

1.200 inches

Detent Quantity:

4

Actuation Method:

Push button

Grip Length:

Between 1.200 inches and 1.220 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank

Shear Strength:

5150 double pound

Shoulder To Head End Distance:

1.550 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.380 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Qq-s-225/5 t4 federal specification 1st material response head or qq-a-225/6 t4 federal specification 2nd material response head or

qq-a-225/9 t6 federal specification 3rd material response head or qq-a-591 federal specification 4th material response head

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response head

Style Designator:

Button

Specification Data:

80205-nas1333 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

NSN 5315-01-312-7098

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

