

View Online at <https://aerobasegroup.com/nsn/5315-01-315-5630>

First End Style:

Chamfered

Second End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.620 inches

Shank Length:

Between 1.130 inches and 1.150 inches

Shoulder Diameter:

0.430 inches

Shank Diameter:

0.400 inches

Overall Length:

2.700 inches

Undercut Diameter:

Between 0.280 inches and 0.300 inches

Undercut Width:

Between 0.050 inches and 0.070 inches

First End Taper Length:

0.040 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

55.0 rockwell c

Thread Size:

0.250 inches

Second Shank Diameter:

0.250 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second Shank Length:

0.750 inches

Material:

Steel comp 4140 or steel comp e4340

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5626 spec.