

View Online at <https://aerobasegroup.com/nsn/5315-01-315-9009>

**Head Diameter:**

Between 0.805 inches and 0.870 inches

**Shank Diameter:**

Between 0.6220 inches and 0.6235 inches

**Ring Handle Diameter:**

Between 1.312 inches and 1.500 inches

**Detent Quantity:**

2

**Lanyard Length:**

10.000 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 2.000 inches and 2.020 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

51200 double pound

**Shoulder To Head End Distance:**

1.250 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.750 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response shank

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.