

View Online at <https://aerobasegroup.com/nsn/5315-01-315-9009>

Head Diameter:

Between 0.805 inches and 0.870 inches

Shank Diameter:

Between 0.6220 inches and 0.6235 inches

Ring Handle Diameter:

Between 1.312 inches and 1.500 inches

Detent Quantity:

2

Lanyard Length:

10.000 inches

Actuation Method:

Push button

Grip Length:

Between 2.000 inches and 2.020 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

51200 double pound

Shoulder To Head End Distance:

1.250 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.750 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response shank

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification all treatment responses spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.