

View Online at <https://aerobasegroup.com/nsn/5315-01-317-2700>

**First End Style:**

Square

**Head Style:**

Square

**Under Head Length:**

0.560 inches

**First Step Diameter:**

0.244 inches

**First Step Length:**

0.058 inches

**Second Step Diameter:**

Between 0.1867 inches and 0.1877 inches

**Second Step Length:**

0.502 inches

**Head Width:**

Between 0.372 inches and 0.375 inches

**Hole Arrangement Style:**

Drilled through head

**First Hole Diameter:**

0.164 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.755 inches

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Surface Finish:**

32.0 microinches shank end

**Special Features:**

0.029 in. In 0.032 in. Maximum wide undercut 0.147 in. Min 0.149 in. Maximum dia. Undercut located at shank end

**Height:**

Between 0.350 inches and 0.370 inches

**Material:**

Steel comp 416

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0