## NSN 5315-01-317-2703

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-317-2703

First End Style:

Slotted

Second End Style:

Square

Thread Class:

2a

## **Thread Direction:**

**Right-hand** 

Thread Length:

0.281 inches

Shank Length:

4.500 inches

Shoulder Diameter:

0.312 inches

Shank Diameter:

Between 0.136 inches and 0.138 inches

**Overall Length:** 

4.593 inches

First End Slot Width:

Between 0.036 inches and 0.056 inches

First End Slot Depth:

Between 0.052 inches and 0.072 inches

## Second End Relationship With First End:

Not identical

Thread Size:

0.138 inches

First End Location:

Unthreaded end

Surface Finish:

63.0 microinches long end

#### Material:

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

Material Specification:

Aisi assn standard all material responses

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Dod-p-16232, ty m, cl 1 national specification single treatment response

#### Style Designator:

Shoulder

**Thread Series Designator:** 

Unc

# NSN 5315-01-317-2703

Headless Shoulder Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

