NSN 5315-01-317-9115

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-317-9115

| First End Style: |
|---|
| Chamfered |
| Second End Style: |
| Square |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.620 inches |
| Shank Length: |
| 1.000 inches |
| Shoulder Diameter: |
| 0.375 inches |
| Shank Diameter: |
| 0.312 inches |
| Overall Length: |
| 1.750 inches |
| Hole Arrangement Style: |
| Drilled shank threaded pin |
| First Hole Diameter: |
| Between 0.123 inches and 0.128 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.630 inches |
| First End Taper Length: |
| 0.250 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.312 inches |
| First End Location: |
| Chamfered end |
| First End Taper Angle: |
| 20.0 degrees |
| Material: |
| Steel comp 630 |
| Material Specification: |
| Mil-c-24111, type 1, cond 3 military specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35, type 4 federal specification single treatment response |

NSN 5315-01-317-9115

Headless Shoulder Pin - Page 2 of 2



| Style Designator: |
|---------------------------|
| Shoulder |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |

Mil-std (military Standard):

Mil-c-24111 spec.