

View Online at <https://aerobasegroup.com/nsn/5315-01-318-2113>

First End Style:

Chamfered

Head Style:

Flat fillister

Diameter:

Between 1.161 inches and 1.170 inches

Undercut Diameter:

Between 1.066 inches and 1.075 inches

Under Head Length:

Between 2.952 inches and 2.973 inches

Undercut Radius:

Between 0.118 inches and 0.126 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.334 inches and 0.347 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.393 inches and 0.394 inches

First End Taper Length:

0.052 inches

Grip Length:

Between 2.559 inches and 2.579 inches

First End Taper Angle:

Between 42.0 degrees and 48.0 degrees

Pin Head Diameter:

1.378 inches

Special Features:

0.275 in. Min. 0.315 in. Max. Hole on head

Height:

Between 0.650 inches and 0.669 inches

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, cl 2, type 2 federal specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0