NSN 5315-01-318-4823

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-318-4823

First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.495 inches and 0.515 inches Shank Length: Between 0.530 inches and 0.550 inches Shoulder Width Across Flats: Between 0.615 inches and 0.635 inches Shank Diameter: Between 0.3731 inches and 0.3735 inches **Overall Length:** Between 1.280 inches and 1.340 inches **End Application:** 68a312006/radome nose barrel First End Taper Length: 0.140 inches Second End Taper Length: Between 0.046 inches and 0.076 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches Second Shank Diameter: 0.3742 inches **First End Location:** Unthreaded end First End Taper Angle: Between 29.5 degrees and 30.5 degrees Second End Taper Angle: 45.0 degrees Second Shank Length: Between 0.660 inches and 0.680 inches Material: Titanium alloy **Material Specification:** Mil-t-9047, cond anl military specification single material response

NSN 5315-01-318-4823

Headless Shoulder Pin - Page 2 of 2

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-9047 spec.

