NSN 5315-01-318-4826

Headless Shoulder Pin - Page 1 of 2

First End Style: Chamfered



View Online at https://aerobasegroup.com/nsn/5315-01-318-4826

Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.507 inches and 0.527 inches
Shank Length:
Between 0.430 inches and 0.450 inches
Shoulder Width Across Flats:
Between 0.490 inches and 0.510 inches
Shank Diameter:
Between 0.2546 inches and 0.2550 inches
Overall Length:
Between 1.290 inches and 1.350 inches
End Application:
68a312006/radome nose barrel
First End Taper Length:
0.140 inches
Second End Taper Length:
Between 0.040 inches and 0.070 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
Second Shank Diameter:
0.2492 inches
First End Location:
Unthreaded end
First End Taper Angle:
Between 29.5 degrees and 30.5 degrees
Second End Taper Angle:
45.0 degrees
Second Shank Length:
Between 0.770 inches and 0.790 inches
Material:
Titanium alloy
Material Specification:
Mil-t-9047, cond anl military specification single material response

NSN 5315-01-318-4826

Headless Shoulder Pin - Page 2 of 2



Shoulder
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

Mil-std (military Standard):

Style Designator:

Mil-t-9047 spec.