NSN 5315-01-318-4826

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-318-4826

First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.507 inches and 0.527 inches Shank Length: Between 0.430 inches and 0.450 inches **Shoulder Width Across Flats:** Between 0.490 inches and 0.510 inches Shank Diameter: Between 0.2546 inches and 0.2550 inches **Overall Length:** Between 1.290 inches and 1.350 inches **End Application:** 68a312006/radome nose barrel First End Taper Length: 0.140 inches Second End Taper Length: Between 0.040 inches and 0.070 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches Second Shank Diameter: 0.2492 inches **First End Location:** Unthreaded end First End Taper Angle: Between 29.5 degrees and 30.5 degrees Second End Taper Angle: 45.0 degrees Second Shank Length: Between 0.770 inches and 0.790 inches Material: Titanium alloy **Material Specification:** Mil-t-9047, cond anl military specification single material response

NSN 5315-01-318-4826

Headless Shoulder Pin - Page 2 of 2

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-9047 spec.

