

View Online at <https://aerobasegroup.com/nsn/5315-01-319-2199>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.000 inches

**Pinlength:**

1.560 inches

**Pindiameter:**

Between 0.3660 inches and 0.3750 inches

**Second End Slot Width:**

Between 0.060 inches and 0.090 inches

**First End Taper Length:**

0.040 inches

**Second End Slot Depth:**

0.120 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

38.0 rockwell c and 42.0 rockwell c

**Thread Size:**

0.375 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Pin Grip Length:**

0.560 inches

**Material:**

Steel comp 4140 or steel comp 8640

**Material Specification:**

Astm a322 assn standard all material responses or astm a331 assn standard all material responses

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification 1st treatment response or astm b633 type 2 assn standard 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0