NSN 5315-01-320-7294

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-320-7294 First End Style: Slotted Second End Style: Square **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Shoulder Diameter:** 0.375 inches **Overall Length:** 1.687 inches First Step Diameter: Between 0.246 inches and 0.248 inches **Second Step Diameter:** Between 0.213 inches and 0.218 inches **Second Step Length:** Between 0.270 inches and 0.275 inches **Third Step Diameter:** Between 0.186 inches and 0.187 inches Third Step Length: 0.375 inches **Shoulder Length:** 0.125 inches First End Slot Width: 0.062 inches First End Slot Depth: 0.093 inches Second End Relationship With First End: Not identical **Hardness Rating:** 36.0 rockwell c and 42.0 rockwell c **Thread Size:** 0.190 inches **First End Location:** Unthreaded end Material: Steel comp 630

Material Specification:
Aisi assn standard single material response

NSN 5315-01-320-7294

Headless Shoulder Pin - Page 2 of 2



_	-	
SIII	taca	Treatment:
Jui	Iacc	i i cauliciii.

Passivate

Surface Treatment Specification:

Qq-p-35, type 1 federal specification 1st treatment response or qq-p-35, type 2 federal specification 2nd treatment response or qq-p-35, type 3 federal specification 3rd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0