

View Online at <https://aerobasegroup.com/nsn/5315-01-322-7383>

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.300 inches and 1.320 inches

**Actuation Type:**

Pull

**Shear Strength:**

14400 double pound

**Shoulder To Head End Distance:**

1.380 inches

**Pin Center To Handle End Distance:**

Between 1.450 inches and 1.550 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.250 inches and 0.350 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle or cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification 1st treatment response spindle or qq-p-416, type 2, cl 2 federal specification 2nd treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6736 spec.