

View Online at <https://aerobasegroup.com/nsn/5315-01-323-1074>

Head Diameter:

0.505 inches

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Grip Length:

Between 3.100 inches and 3.120 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank 36.0 rockwell c spindle and 40.0 rockwell c spindle

Shoulder To Head End Distance:

0.935 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.440 inches

Material:

Steel comp 4130 shank steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response shank mil-s-6758 military specification single material response spindle or mil-s-6736 military specification single material response spindle

Surface Treatment:

Cadmium shank and chromate shank cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shank qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.