NSN 5315-01-323-9056

Headless Grooved Pin - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5315-01-323-9056

First End Style: Square Overall Length: Between 0.238 inches and 0.242 inches Diameter: Between 0.152 inches and 0.154 inches Effective Length: Between 0.081 inches and 0.084 inches Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure: Demilitarization:	
Overall Length:Between 0.238 inches and 0.242 inchesDiameter:Between 0.152 inches and 0.154 inchesEffective Length:Between 0.081 inches and 0.084 inchesUndercut Diameter:Between 0.097 inches and 0.098 inchesUndercut Width:Between 0.073 inches and 0.076 inchesSecond End Relationship With First End:IdenticalHardness Rating:50.0 rockwell c and 54.0 rockwell cFirst End Location:Both endsMaterial:Steel comp 440cMaterial Specification:Ams 5630 assn standard single material responseStyle Designator:GrooveShelf Life:N/aUnit Of Measure:	First End Style:
Between 0.238 inches and 0.242 inches Diameter: Between 0.152 inches and 0.154 inches Effective Length: Between 0.081 inches and 0.084 inches Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Square
Diameter: Between 0.152 inches and 0.154 inches Effective Length: Between 0.081 inches and 0.084 inches Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Overall Length:
Between 0.152 inches and 0.154 inches Effective Length: Between 0.081 inches and 0.084 inches Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Between 0.238 inches and 0.242 inches
Effective Length: Between 0.081 inches and 0.084 inches Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Diameter:
Between 0.081 inches and 0.084 inches Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Between 0.152 inches and 0.154 inches
Undercut Diameter: Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Effective Length:
Between 0.097 inches and 0.098 inches Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Between 0.081 inches and 0.084 inches
Undercut Width: Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Undercut Diameter:
Between 0.073 inches and 0.076 inches Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Between 0.097 inches and 0.098 inches
Second End Relationship With First End: Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Undercut Width:
Identical Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Between 0.073 inches and 0.076 inches
Hardness Rating: 50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Second End Relationship With First End:
50.0 rockwell c and 54.0 rockwell c First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Identical
First End Location: Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Hardness Rating:
Both ends Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure: 	50.0 rockwell c and 54.0 rockwell c
Material: Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure: 	First End Location:
Steel comp 440c Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure: 	Both ends
Material Specification: Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Material:
Ams 5630 assn standard single material response Style Designator: Groove Shelf Life: N/a Unit Of Measure: 	Steel comp 440c
Style Designator: Groove Shelf Life: N/a Unit Of Measure:	Material Specification:
Groove Shelf Life: N/a Unit Of Measure:	Ams 5630 assn standard single material response
Shelf Life: N/a Unit Of Measure:	Style Designator:
N/a Unit Of Measure: 	Groove
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A212a0	A212a0