NSN 5315-01-325-5459

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-325-5459 First End Style: Chamfered Second End Style: Chamfered **Shoulder Diameter:** 0.500 inches **Overall Length:** 1.670 inches First Step Diameter: Between 0.249 inches and 0.250 inches **Second Step Diameter:** Between 0.248 inches and 0.250 inches Second Step Length: 0.145 inches Third Step Diameter: 0.190 inches Third Step Length: 0.226 inches **End Application:** Mk93 mod0 fleet exercise sys, torpedo mk50 **Shoulder Length:** 0.095 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Not identical First End Taper Angle: 45.0 degrees **Second End Tip Radius:** 0.030 inches **Second End Taper Angle:** 60.0 degrees Material: Stainless steel **Material Specification:** Astm a582, cl 300 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Style Designator: Shoulder

Qq-p-35 federal specification single treatment response

NSN 5315-01-325-5459

Headless Shoulder Pin - Page 2 of 2



Supplementary Features	Sı	ıppl	eme	ntary	/ Fo	eatı	ires	3:
------------------------	----	------	-----	-------	------	------	------	----

Fourth step length 0.355in; fourth diameter .142min/.144max; 3rd step is threaded-.190-32unf-3a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0