NSN 5315-01-328-1779

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-328-1779 **Head Diameter:** Between 0.312 inches and 0.530 inches **Shank Diameter:** Between 0.1870 inches and 0.1885 inches **Ring Handle Diameter:** 1.060 inches **Detent Quantity: Actuation Method:** Push button **End Application:** Mrap rg-33 **Grip Length:** Between 3.800 inches and 3.820 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shear Strength:** 5150 double pound **Shoulder To Head End Distance:** 0.730 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.230 inches and 0.260 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Bams 5643 military specification all material responses spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5315-01-328-1779

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

spec.