

View Online at <https://aerobasegroup.com/nsn/5315-01-329-4858>

First End Style:

Chamfered

Head Length:

33.0 millimeters

Under Head Length:

91.0 millimeters

First Step Diameter:

12.6 millimeters

First Step Length:

40.0 millimeters

Second Step Diameter:

10.0 millimeters

Second Step Length:

51.0 millimeters

Head Width:

21.5 millimeters

End Application:

RECO-IL-AMP-LIFI

First End Taper Length:

2.0 millimeters

First End Taper Angle:

45.0 degrees

Special Features:

Calc. Material: classification and inspection of investment casting will be per class 3, grade c; heat at 1540-1580 deg. F., oil quench, temper 1 hr. Min.; threaded to m10x1-6g; thread lg. ls 45.0 mm.

Height:

16.0 millimeters

Material:

Steel

Material Specification:

Astm a322, grade 4140 assn standard single material response or astm a331, grade 4140 assn standard single material response or mil-s-22141, cmpsn ic4140 military specification single material response

Surface Treatment:

Phosphate manganese or phosphate zinc

Surface Treatment Specification:

Mil-p-16232, class 1, type m orz military specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-22141 spec.