NSN 5315-01-332-7500

Headless Shoulder Pin - Page 1 of 2

First End Style:

Second End Style:

Thread Direction:

Thread Length: 0.300 inches Shank Length:

Square

2a

Chamfered
Thread Class:

Right-hand



View Online at https://aerobasegroup.com/nsn/5315-01-332-7500

Shoulder Diameter: 0.850 inches Shank Diameter: Between 0.310 inches and 0.311 inches Overall Length: 1.550 inches First End Taper Length: 0.035 inches Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Thread Ged First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second End Taper Angle: Second	1.110 inches
Shank Diameter: Between 0.310 inches and 0.311 inches Overall Length: 1.550 inches First End Taper Length: 0.035 inches Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 3.2.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Shoulder Diameter:
Between 0.310 inches and 0.311 inches Overall Length: 1.550 inches First End Taper Length: 0.035 inches Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Thread end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	0.850 inches
Overall Length: 1.550 inches First End Taper Length: 0.035 inches Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 3.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Shank Diameter:
1.550 inches First End Taper Length: 0.035 inches Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Between 0.310 inches and 0.311 inches
First End Taper Length: 0.035 inches Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Overall Length:
Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	1.550 inches
Second End Relationship With First End: Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	First End Taper Length:
Not identical Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	0.035 inches
Thread Size: 0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Second End Relationship With First End:
0.4375 inches Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Not identical
Second Shank Diameter: 0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Thread Size:
0.4375 inches First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	0.4375 inches
First End Location: Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Second Shank Diameter:
Threaded end First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	0.4375 inches
First End Taper Angle: Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	First End Location:
Between 40.0 degrees and 50.0 degrees Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Threaded end
Second End Tip Radius: 0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	First End Taper Angle:
0.050 inches Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Between 40.0 degrees and 50.0 degrees
Surface Finish: 32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Second End Tip Radius:
32.0 microinches long shank Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	0.050 inches
Second End Taper Angle: 15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Surface Finish:
15.0 degrees Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	32.0 microinches long shank
Second Shank Length: 0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	Second End Taper Angle:
0.360 inches Material: Steel comp 303 or steel comp 304 Material Specification:	15.0 degrees
Material: Steel comp 303 or steel comp 304 Material Specification:	Second Shank Length:
Steel comp 303 or steel comp 304 Material Specification:	0.360 inches
Material Specification:	Material:
	Steel comp 303 or steel comp 304
Astm a582 assn standard 1st material response or astm a276 assn standard 2nd material response	Material Specification:
	Astm a582 assn standard 1st material response or astm a276 assn standard 2nd material response

NSN 5315-01-332-7500

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0