NSN 5315-01-333-5736

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-333-5736

| First End Style: |
|--|
| Square internally threaded |
| Second End Style: |
| Chamfered |
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.250 inches |
| Shank Length: |
| 0.443 inches |
| Shoulder Width Across Flats: |
| 0.375 inches |
| Shank Diameter: |
| Between 0.200 inches and 0.202 inches |
| Overall Length: |
| 0.617 inches |
| Second End Taper Length: |
| 0.164 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.138 inches |
| Second Shank Diameter: |
| Between 0.248 inches and 0.250 inches |
| First End Location: |
| Threaded end |
| Second End Tip Radius: |
| 0.045 inches |
| Second Shank Length: |
| 0.109 inches |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582, cond a assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |

Shoulder

NSN 5315-01-333-5736

Headless Shoulder Pin - Page 2 of 2



| Thread | Series | Desi | ignat | or: |
|--------|--------|------|-------|-----|
| | | | | |

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0