NSN 5315-01-334-2885

Headless Shoulder Pin - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5315-01-334-2885 |
|---|
| First End Style: |
| Chamfered |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.175 inches |
| Shoulder Width Across Flats: |
| 0.250 inches |
| Overall Length: |
| 1.674 inches |
| First Step Diameter: |
| Between 0.113 inches and 0.115 inches |
| Second Step Diameter: |
| 0.164 inches |
| Second Step Length: |
| 0.175 inches |
| Third Step Diameter: |
| Between 0.113 inches and 0.115 inches |
| Third Step Length: |
| 0.585 inches |
| Shoulder Length: |
| Between 0.027 inches and 0.037 inches |
| First End Taper Length: |
| 0.032 inches |
| Second End Relationship With First End: |
| Identical |
| Thread Size: |
| 0.164 inches |
| First End Location: |
| Both ends |
| First End Taper Angle: |
| Between 56.0 degrees and 64.0 degrees |
| First End Tip Radius: |
| 0.032 inches |

Material:

Steel comp 303

Special Features: Second step threaded

Material Specification:

Astm a582 cond a assn standard single material response

NSN 5315-01-334-2885

Headless Shoulder Pin - Page 2 of 2

A212a0



| Surface Treatment: | |
|--|--|
| Passivate | |
| Surface Treatment Specification: | |
| Qq-p-35, type 1, 2, 3 or 4 federal specification single treatment response | |
| Style Designator: | |
| Shoulder | |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |