NSN 5315-01-340-2907

Quick Release Pin - Page 1 of 1

A212a0

Mil-s-6758 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5315-01-340-2907 **Shank Diameter:** 25.0 millimeters **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** 21.2 millimeters **Actuation Type:** Push Material: Aluminum alloy a380.0 handlesteel comp 4130 shanksteel comp 440c detentsteel comp 4130 spindlealuminum alloy 2017 buttonsteel comp b1113 ringsteel uns k08500 spring **Material Specification:** Qq-a-591 federal specification single material response handlemil-s-6758 military specification single material response shank or mil-t-6736 military specification single material response shankqq-s-763 federal specification single material response detentmil-s-6758 military specification single material response spindlegq-a-351 federal specification single material response buttongq-s-633 federal specification single material response ringgq-w-470 federal specification single material response spring **Surface Treatment:** Anodize handlecadmium shankpassivate detentcadmium spindleanodize buttoncadmium ringcadmium spring **Surface Treatment Specification:** Mil-a-8625 black military specification single treatment response handleqq-p-416, type 1, class 3 federal specification single treatment response shankmil-s-5002 military specification single treatment response detentqq-p-416, type 1, class 3 federal specification single treatment response spindlemil-a-8625 gold military specification single treatment response buttonqq-p-416, type 1, class 3 federal specification single treatment response ringqq-p-416, type 1, class 3 federal specification single treatment response spring **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig: