NSN 5315-01-340-7086

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-340-7086

Head Diameter:

Between 0.530 inches and 0.630 inches

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Detent Quantity:

2

Actuation Method:

Handle

Grip Length:

Between 3.100 inches and 3.120 inches

Actuation Type:

Pull

Shoulder To Head End Distance:

1.090 inches

Pin Center To Handle End Distance:

1.500 inches

Pin Attachment Type:

Link and ring

Detent To Tapered End Distance:

0.640 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st

material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0