

View Online at <https://aerobasegroup.com/nsn/5315-01-340-7087>

**Head Diameter:**

Between 1.175 inches and 1.330 inches

**Shank Diameter:**

Between 0.9970 inches and 0.9985 inches

**Ring Handle Diameter:**

1.640 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 4.000 inches and 4.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

147000 double pound

**Shoulder To Head End Distance:**

2.000 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.860 inches and 0.890 inches

**Material:**

Steel comp 630 shank steel comp 630 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or st0632 assn standard 2nd material response shank  
ams 5643 assn standard single material response spindle or st0632 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0