

View Online at <https://aerobasegroup.com/nsn/5315-01-340-8770>

**Shank Diameter:**

Between 0.2470 inches and 0.2495 inches

**Button Handle Diameter:**

1.200 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.700 inches and 0.720 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c shank

**Shear Strength:**

9200 double pound

**Shoulder To Head End Distance:**

1.290 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

0.410 inches

**Material:**

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Mas 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shankpassivate spindle

**Style Designator:**

Button

**Specification Data:**

80205-nas1354 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0