

View Online at <https://aerobasegroup.com/nsn/5315-01-340-8770>

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Button Handle Diameter:

1.200 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.700 inches and 0.720 inches

Actuation Type:

Pull and push

Hardness Rating:

40.0 rockwell c shank

Shear Strength:

9200 double pound

Shoulder To Head End Distance:

1.290 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Mas 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Style Designator:

Button

Specification Data:

80205-nas1354 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0