

View Online at <https://aerobasegroup.com/nsn/5315-01-341-7008>

Handle Length:

Between 1.700 inches and 2.000 inches

Shank Diameter:

Between 0.3720 inches and 0.3745 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.700 inches and 0.720 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shoulder To Head End Distance:

1.730 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

0.510 inches

Material:

Steel comp 4130 shank or steel comp 4135 shank or steel comp 4130 shanksteel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank or mil-t-6736 military specification 3rd material response shankmil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium shank and chromate shankcadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification all treatment responses shankqq-p-416 type 2 cl 2 federal specification all treatment responses spindle

Style Designator:

T handle

Specification Data:

80205-nas1356 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.