

View Online at <https://aerobasegroup.com/nsn/5315-01-341-7008>

**Handle Length:**

Between 1.700 inches and 2.000 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3745 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.700 inches and 0.720 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank

**Shoulder To Head End Distance:**

1.730 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

0.510 inches

**Material:**

Steel comp 4130 shank or steel comp 4135 shank or steel comp 4130 shanksteel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank or mil-t-6736 military specification 3rd material response shankmil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium shank and chromate shankcadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses shankqq-p-416 type 2 cl 2 federal specification all treatment responses spindle

**Style Designator:**

T handle

**Specification Data:**

80205-nas1356 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.