## NSN 5315-01-341-7596

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-341-7596 First End Style: Chamfered Second End Style: Chamfered **Thread Pitch Diameters:** +0.2810/+0.2825 inches **Thread Direction:** Right-hand Thread Length: 0.531 inches **Shank Length:** 0.477 inches **Shoulder Width Across Flats:** Between 0.492 inches and 0.502 inches **Shank Diameter:** Between 0.306 inches and 0.308 inches **Overall Length:** Between 1.270 inches and 1.310 inches **Undercut Diameter:** Between 0.205 inches and 0.225 inches **Undercut Width:** Between 0.084 inches and 0.104 inches First End Taper Length: Between 0.050 inches and 0.070 inches **Second End Taper Length:** Between 0.030 inches and 0.060 inches Thready Qty Per Inch (tpi): 18 Second End Relationship With First End: Not identical **Thread Size:** 0.3125 inches **Second Shank Diameter:** 0.312 inches First End Location: Unthreaded end First End Taper Angle:

Between 15.0 degrees and 25.0 degrees
Second End Taper Angle:
Between 30.0 degrees and 60.0 degrees
Second Shank Length:
0.531 inches

## NSN 5315-01-341-7596

Headless Shoulder Pin - Page 2 of 2



Material:
Steel comp 8740
Style Designator:
Undercut
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A212a0