## NSN 5315-01-342-2064

Headless Shoulder Pin - Page 1 of 2

First End Style: Chamfered

Second End Style:



View Online at https://aerobasegroup.com/nsn/5315-01-342-2064

Chamfered
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.479 inches
Shank Length:
0.479 inches
Shoulder Diameter:
Between 0.677 inches and 0.687 inches
Shank Diameter:
0.625 inches
Overall Length:
Between 3.090 inches and 3.290 inches
Undercut Diameter:
Between 0.491 inches and 0.501 inches
Undercut Width:
0.271 inches
First End Taper Length:
Between 0.062 inches and 0.067 inches
Second End Taper Length:
0.500 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.625 inches
First End Location:
Threaded end
First End Taper Angle:
Between 35.0 degrees and 45.0 degrees
Second End Tip Radius:
0.030 inches
Second End Taper Angle:
25.0 degrees
Material:
Steel comp 303
Material Specification:

Astm a582, cond a assn standard single material response

## NSN 5315-01-342-2064

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 4 federal specification single treatment response
Style Designator:
Undercut
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0