

View Online at <https://aerobasegroup.com/nsn/5315-01-346-0036>

**Head Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.3095 inches and 0.3120 inches

**Ring Handle Diameter:**

1.223 inches

**Detent Quantity:**

4

**Actuation Method:**

Push button

**Grip Length:**

Between 1.700 inches and 1.720 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank

**Shear Strength:**

14400 double pound

**Shoulder To Head End Distance:**

1.490 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

0.400 inches

**Material:**

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shankpassivate spindle

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1335 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0