

View Online at <https://aerobasegroup.com/nsn/5315-01-346-5610>

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

Between 0.875 inches and 1.135 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 4.000 inches and 4.020 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank 36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

18400 double pound

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

Material:

Steel comp 4130 shank steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium shank and chromate shank cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shank qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.