# NSN 5315-01-347-4151

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-347-4151

#### Head Diameter:

Between 1.200 inches and 1.280 inches

#### Handle Length:

Between 2.750 inches and 2.875 inches

#### Shank Diameter:

Between 0.9970 inches and 0.9985 inches

#### **Detent Quantity:**

2

#### **Actuation Method:**

Push button

Grip Length:

Between 6.500 inches and 6.520 inches

#### Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

#### Shear Strength:

147000 double pound

#### Shoulder To Head End Distance:

1.830 inches

#### Pin Attachment Type:

Link or ring

#### **Detent To Tapered End Distance:**

1.100 inches

## Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

#### Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st

material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate shankpassivate spindle

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

#### Style Designator:

T handle

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A212a0