

View Online at <https://aerobasegroup.com/nsn/5315-01-347-4167>

Handle Length:

Between 1.750 inches and 1.815 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.100 inches and 3.120 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

9200 double pound

Shoulder To Head End Distance:

1.270 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0