

View Online at <https://aerobasegroup.com/nsn/5315-01-347-6574>

**First End Style:**

Chamfered

**Head Style:**

Round w/wrench flats

**Diameter:**

Between 0.2475 inches and 0.2485 inches

**Effective Length:**

Between 0.310 inches and 0.320 inches

**Undercut Diameter:**

Between 0.130 inches and 0.145 inches

**Under Head Length:**

Between 0.540 inches and 0.570 inches

**Undercut Width:**

Between 0.020 inches and 0.040 inches

**Second Undercut Width:**

Between 0.020 inches and 0.040 inches

**Second Undercut Diameter:**

Between 0.200 inches and 0.215 inches

**First End Taper Length:**

Between 0.020 inches and 0.040 inches

**Width Across Flats:**

Between 0.270 inches and 0.280 inches

**Pin Head Diameter:**

Between 0.380 inches and 0.390 inches

**Special Features:**

Uplating not permitted on threads. Opposite head is threaded end. .190-32unf-3a. Center of through hole .070-.080 is located .473 from base of head in threaded area. Both grooves have an unknown radius surfaceroughness 63 microfinish

**Height:**

Between 0.030 inches and 0.040 inches

**Material:**

Nickel alloy uns n07001

**Surface Treatment:**

Nickel

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0