

View Online at <https://aerobasegroup.com/nsn/5315-01-347-6574>

First End Style:

Chamfered

Head Style:

Round w/wrench flats

Diameter:

Between 0.2475 inches and 0.2485 inches

Effective Length:

Between 0.310 inches and 0.320 inches

Undercut Diameter:

Between 0.130 inches and 0.145 inches

Under Head Length:

Between 0.540 inches and 0.570 inches

Undercut Width:

Between 0.020 inches and 0.040 inches

Second Undercut Width:

Between 0.020 inches and 0.040 inches

Second Undercut Diameter:

Between 0.200 inches and 0.215 inches

First End Taper Length:

Between 0.020 inches and 0.040 inches

Width Across Flats:

Between 0.270 inches and 0.280 inches

Pin Head Diameter:

Between 0.380 inches and 0.390 inches

Special Features:

Uplating not permitted on threads. Opposite head is threaded end. .190-32unf-3a. Center of through hole .070-.080 is located .473 from base of head in threaded area. Both grooves have an unknown radius surfaceroughness 63 microfinish

Height:

Between 0.030 inches and 0.040 inches

Material:

Nickel alloy uns n07001

Surface Treatment:

Nickel

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0