

View Online at <https://aerobasegroup.com/nsn/5315-01-349-9353>

**Head Diameter:**

Between 0.310 inches and 0.530 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

1.060 inches

**Detent Quantity:**

4

**Actuation Method:**

Push button

**Grip Length:**

Between 0.500 inches and 0.520 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

9200 double pounds per square inch

**Shoulder To Head End Distance:**

0.780 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

1.000 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0