## NSN 5315-01-350-0386

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-350-0386 First End Style: Countersunk Second End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Shank Length:** Between 0.095 inches and 0.105 inches **Shoulder Width Across Flats:** Between 0.182 inches and 0.192 inches **Shank Diameter:** 0.930 inches **Overall Length:** 0.350 inches Second End Taper Length: 0.031 inches **Second End Relationship With First End:** Not identical **Thread Size:** 0.312 inches First End Location: Countersunk end First End Countersink Angle: 120.0 degrees First End Countersink Diameter: Between 0.040 inches and 0.050 inches **Second End Taper Angle:** 45.0 degrees Material: Steel comp 303 **Material Specification:** Astm a582, cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-std-171 military standard single treatment response

**Style Designator:** 

Shoulder

## NSN 5315-01-350-0386

Headless Shoulder Pin - Page 2 of 2



Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

Mil-std-171 spec.