

View Online at <https://aerobasegroup.com/nsn/5315-01-351-8187>

**Shank Diameter:**

Between 0.5585 inches and 0.5616 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.400 inches and 1.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

46700 double pound

**Shoulder To Head End Distance:**

1.620 inches

**Pin Center To Handle End Distance:**

2.000 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

0.600 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Specification Data:**

80205-nas1339 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0