

View Online at <https://aerobasegroup.com/nsn/5315-01-352-2675>

Shank Diameter:

Between 0.3095 inches and 0.3120 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.700 inches and 1.720 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

128000 double pound

Shoulder To Head End Distance:

1.550 inches

Pin Center To Handle End Distance:

1.780 inches

Pin Attachment Type:

Link and ring

Detent To Tapered End Distance:

0.400 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Cadmium shank and chromate shank cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shank qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

L handle

Specification Data:

80205-nas1335 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0