

View Online at <https://aerobasegroup.com/nsn/5315-01-352-2675>

**Shank Diameter:**

Between 0.3095 inches and 0.3120 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.700 inches and 1.720 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

128000 double pound

**Shoulder To Head End Distance:**

1.550 inches

**Pin Center To Handle End Distance:**

1.780 inches

**Pin Attachment Type:**

Link and ring

**Detent To Tapered End Distance:**

0.400 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Cadmium shank and chromate shank cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response shank qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

L handle

**Specification Data:**

80205-nas1335 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0