

View Online at <https://aerobasegroup.com/nsn/5315-01-353-2085>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Button Handle Diameter:**

Between 1.300 inches and 1.400 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 7.000 inches and 7.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

36800 double pound

**Shoulder To Head End Distance:**

1.190 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel comp 630 shank and steel comp 632 shank steel comp 630 spindle and steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0