NSN 5315-01-353-2086

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-353-2086 **Head Diameter:** Between 1.214 inches and 1.224 inches **Shank Diameter:** Between 0.9970 inches and 0.9985 inches **Ring Handle Diameter:** 1.312 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 6.900 inches and 6.920 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c shank40.0 rockwell c spindle **Shear Strength:** 147000 double pound **Shoulder To Head End Distance:** 1.700 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** 1.100 inches Material: Steel comp 630 shank and steel comp 632 shanksteel comp 630 spindle and steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response shank or asm 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate shankpassivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:**

Fiig: A212a0

No

Demilitarization: