NSN 5315-01-353-2086

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-353-2086

Head Diameter:

Between 1.214 inches and 1.224 inches

Shank Diameter:

Between 0.9970 inches and 0.9985 inches

Ring Handle Diameter:

1.312 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 6.900 inches and 6.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

Shear Strength:

147000 double pound

Shoulder To Head End Distance:

1.700 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

1.100 inches

Material:

Steel comp 630 shank and steel comp 632 shanksteel comp 630 spindle and steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or asm 5657 assn standard 2nd material response shankams 5643 assn standard 1st

material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0