NSN 5315-01-354-3831

Headless Shoulder Pin - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5315-01-354-3831 | |
|---|--|
| First End Style: | |
| Chamfered | |
| Second End Style: | |
| Square | |
| Thread Class: | |
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.300 inches | |
| Shank Length: | |
| Between 0.710 inches and 0.730 inches | |
| Shoulder Diameter: | |
| 0.312 inches | |
| Shank Diameter: | |
| Between 0.205 inches and 0.210 inches | |
| Overall Length: | |
| Between 1.010 inches and 1.020 inches | |
| Internal Drive Style: | |
| Torque | |
| First End Taper Length: | |
| 0.046 inches | |
| Thready Qty Per Inch (tpi): | |
| 14 | |
| Second End Relationship With First End: | |
| Not identical | |
| Thread Size: | |
| 0.312 inches | |
| First End Location: | |
| Unthreaded end | |
| First End Taper Angle: | |
| 45.0 degrees | |
| Surface Finish: | |
| 63.0 microinches shank end | |
| Special Features: | |

0.312 inch drilled hole on threaded end

Material:

Steel comp 303 and steel comp 303se

Material Specification:

Astm a582 assn standard all material responses

Surface Treatment:

Passivate

NSN 5315-01-354-3831

Headless Shoulder Pin - Page 2 of 2



| Style Designator: |
|---------------------------|
| Shoulder |
| Thread Series Designator: |
| Uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

Fiig:

A212a0