NSN 5315-01-355-8888

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-355-8888

First End Style:
Square
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.345 inches
Shank Length:
0.470 inches
Shoulder Width Across Flats:
0.375 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Overall Length:
0.973 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.076 inches and 0.086 inches
Distance From Centerline Of Hole To End Of Pin:
0.140 inches
Second End Taper Length:
Between 0.170 inches and 0.210 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.190 inches
Second Shank Diameter:
Between 0.1851 inches and 0.1863 inches
First End Location:
Threaded end
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
0.440 inches
Special Features:
Rolled raius 0.040in. Max. On both shanks ajacent to shoulder
Material:
Steel comp 302 or steel comp 304 or steel comp 303se

NSN 5315-01-355-8888

Headless Shoulder Pin - Page 2 of 2



۱	/late	rial	Sn	ecif	icat	ion	
١	nate	ııaı	OD	CUII	ıvaı	.1011	٠

Qq-s-763 cond b&j bcqq-s-763 cond b&jfdmca1r mms265 cagec 76301 federal specification 1st material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A212a0