

View Online at <https://aerobasegroup.com/nsn/5315-01-355-9482>

Head Diameter:

0.750 inches

Shank Diameter:

0.250 inches

Ring Handle Diameter:

1.200 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.247 inches and 0.249 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

8200 double pounds per square inch

Shoulder To Head End Distance:

1.730 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 8630 head or steel comp 4130 headsteel comp 4130 shank or steel comp 4135 shanksteel comp 4130 spindlesteel

Material Specification:

Mil-t-6732 military specification 1st material response head or mil-s-6758 federal specification 2nd material response headmil-s-6758 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank or mil-t-6736 military specification 2nd material response shankmil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Style Designator:

Ring handle

Specification Data:

80205-nas1354 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6732 spec.