

View Online at <https://aerobasegroup.com/nsn/5315-01-357-7898>

**Handle Length:**

2.345 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Lanyard Length:**

12.000 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 4.000 inches and 4.020 inches

**Actuation Type:**

Push

**Shear Strength:**

32800 double pound

**Shoulder To Head End Distance:**

1.600 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Special Features:**

Hook or ring attached

**Material:**

Steel comp 4130 shanksteel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shankmil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium shank and chromate shankcadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response shankqq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6736 spec.