## NSN 5315-01-357-7898

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-357-7898 **Handle Length:** 2.345 inches **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Detent Quantity:** Lanyard Length: 12.000 inches **Actuation Method:** Push button **Grip Length:** Between 4.000 inches and 4.020 inches **Actuation Type:** Push **Shear Strength:** 32800 double pound **Shoulder To Head End Distance:** 1.600 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** Between 0.430 inches and 0.460 inches **Special Features:** Hook or ring attached Material: Steel comp 4130 shanksteel comp 4130 spindle **Material Specification:** Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shankmil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium shank and chromate shankcadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response shankqq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure:** 

Fiig: A212a0

No

**Demilitarization:** 

## NSN 5315-01-357-7898

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6736 spec.